

W331

Widescreen, bright, vibrant and Portable

- Bright WXGA projector 3300 ANSI Lumens
- Accurate colours sRGB
- Easy connectivity HDMI, VGA, 2W speaker
- Lightweight and portable



















W331

Widescreen, bright, vibrant and portable

Project bright vibrant presentations in HD effortlessly any time on day. Designed for meeting rooms and classrooms, the W331 boasts sRGB accurate true to life colour reproduction, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

This projector is easy to connect to with multiple inputs and a built-in speaker. Perfect for connecting a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

Amazing colours

For vibrant, natural looking images, Optoma projectors incorporate BrilliantColor™ multi-colour processing technology. This projector also conforms to sRGB standard to produce the most realistic true to life colours possible.





Energy saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance

High contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.





Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.

Wireless presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the WPS Wireless Adapter (sold separately) - you can connect and display presentations wirelessly from a laptop, PC or mobile device.

Integrated speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

Eco AV mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

Auto power off

There may be instances when the projector is left running when not in use. To help save energy, the "Auto Power Off" feature automatically turns off the projector after a set period of time if it is not being used

Long lamp life

Reduce the number of lamp changes with lamp life of up to 10,000 hours² using the Education Cycle.

Colour guarantee

Enjoy dazzling colours for years to come; guaranteed by Optoma for five years' consistent performance.





Wireless

Stream Full 1080p 3D content to your projector wirelessly; eliminating the hassle and extra cost of installing long cables, the WHD200 (sold separately) allows you to connect a Blu-ray[™] player, set-top box, gaming console or AV receiver instantly.

W331 Specification

Native Resolution WXGA 1280 x 800 Brightness ¹ (Bright Mode) 3300 ANSI Lumens Contrast 22,000:1 Lamp Life ² Eco+/Dynamic/Eco/Bright 8000/7000/6000/5000 (hrs) Throw Ratio 1.55 – 1.73:1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB serving Speaker Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 – 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 – 12m Projection Lens F/2.5~2.67; f=21.86~24mm Uniformity 75%	ice
Contrast 22,000:1	ice
Lamp Life ² Eco+/Dynamic/Eco/Bright 8000/7000/6000/5000 (hrs) Throw Ratio 1.55 – 1.73:1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB services Speaker 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 – 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 – 12m Projection Lens F/2.5~2.67; f=21.86~24mm	ice
Throw Ratio 1.55 – 1.73:1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB services Speaker 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	ice
Throw Ratio 1.55 – 1.73:1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB services Speaker 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	ice
I/O Connectors HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB services Speaker 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	ice
Speaker 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	ice
Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 0.68 – 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 – 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Offset 115% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Projection Screen Size 0.68 – 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 – 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Projection Distance 1 – 12m Projection Lens F/2.5~2.67; f=21.86~24mm	
Projection Lens F/2.5~2.67; f=21.86~24mm	
Official transfer of the Control of	
Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac	
Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz)	.4MHz, 480i/p,
3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3 games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.	D™ and 3D
3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60	
Horizontal Scan Rate 15.3 - 91.1kHz	
Vertical Scan Rate 24 - 85Hz (120Hz for 3D)	
Displayable Colours 1073.4 Million	
Noise Level (Eco mode) 29dB	
Power Supply 100-240V, 50-60Hz	
Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby)	
Lamp Type 195W	
Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m	
Security Security Security par, Kensington lock, password protection	
On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Pol Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Tu Vietnamese, Romanian, Indonesian	
Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual	
Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount	
Optional Wireless Yes	
RoHS Compliant	



Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

 2 Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

10/05/2016 00:14